

Description

KMC REE-3214/3222 Multi-Voltage Relays are UL Listed relays packaged in a small protective case that can be either panel or conduit mounted. The multi-voltage relay coils and relay contact outputs have color-coded wires for simplified installation. The relays also have visible LEDs that indicate when the relays are energized.

The REE-3214 has a true manual override Hand-Off-Auto switch, and the REE-3222 has a true manual override Hand-Off-Auto switch on relay #1. Both models have built-in transient protection.

Features

- ◆ Built-in transient protection
- ◆ Status LEDs indicate relay activity
- ◆ Hand-Off-Auto Override switch
- ◆ Protective cases
- ◆ Simple installation

Specifications

Coil Inputs	10–30 VAC/VDC and 120 VAC
Coil Currents	22 mA @ 10 VDC 28 mA @ 12 VDC 35 mA @ 24 VDC 37 mA @ 30 VDC 32 mA @ 9 VAC 40 mA @ 12 VAC 48 mA @ 24 VAC 55 mA @ 30 VAC 37 mA @ 120 VAC
Models	REE-3214 SPDT (N.O.) w/override REE-3222 1-SPDT (N.O.) w/override 1-SPDT
Contact Ratings	10 A Resistive, 125/250 VAC



Coil Wiring

REE-3214

Common	White/Red
10-30 V	White/Brown
120V	White/Gray

REE-3222

Relay #1	
Common	Blue
10-30 V	Brown
120 V	Gray
Relay #2	
Common	Yellow
10-30 V	Orange
120 V	Purple

Contact Wiring

REE-3214

Common	Blue
Norm. Open	Blue

REE-3222

Relay #1	
Common	White/Violet
Norm. Open	White/Violet
Relay #2	
Common	White/Black
Norm. Closed	White/Blue
Norm. Open	White/Yellow

Specifications (Continued)

Wire	18 AWG, 16" (40.64 cm) Length
Mounting	Panel or conduit, hardware included
Dimensions	4" x 4" x 1.8" (101.6 mm x 101.6 mm x 45.72 mm)
Weights	1.03 lbs (.467 kg)
Material	Black ABS

KMC Controls, Inc.
19476 Industrial Drive
New Paris, IN 46553
574.831.5250
www.kmccontrols.com